

# CLEANING SEALING & AFTERCARE

## GROUT HAZE & LIMESCALE REMOVER TECHNICAL DATA SHEET

REF: LTP/38/5

Jan 2024



### LTP GROUT HAZE & LIMESCALE REMOVER

#### Interior & Exterior use

For use on all types of glazed and polished porcelain, glazed ceramic, slate, quarry tiles, brick, mosaics, terracotta, granite and unpolished natural stones.

A ready to use first wash cleaner for removing cement-based grout haze from the surface of tiles without affecting the joint. Ideal for cleaning grout application tools. Periodic cleaning helps to control and remove hard water stains and limescale.

#### Directions for use:

Always test/practice on an inconspicuous area before proceeding to ensure that the finished result is satisfactory.

Shake container well before use.

#### Removing grout films:

Wait for the grout to 'firm off' in the joint before application.

Spray and wipe the surface using a micro-fibre cloth. Rinse the cloth in water, wring out and repeat until surfaces are free from cement residues. For older stubborn residues spray on and scrub immediately using a white nylon scrubbing pad. Wipe away the released residues using a micro-fibre cloth. No need to rinse.

#### Removing hard water stains and limescale:

Spray onto the surface and scrub immediately using white nylon scrubbing pad. Wipe away the released residues using a micro-fibre cloth. Rinse and leave to dry.

#### Coverage M<sup>2</sup> per application (approx.)

|                                | 500ml                  |
|--------------------------------|------------------------|
| Cement based grout films       | up to 10m <sup>2</sup> |
| Limescale and hardwater stains | up to 15m <sup>2</sup> |

#### Storage information:

Store in a cool, dry, frost free environment ideally at 5 - 25°C  
Shelf life up to 4 years if container is unopened.

#### Notes:

- Not suitable for use on stone surfaces that are **polished, (i.e. polished marble, travertine or limestone)**
- Sealed natural stone surfaces should be re-sealed after cleaning with this product.
- Application does not affect chrome or stainless-steel fixtures or fittings.
- Biodegradable solution does not emit harmful fumes.
- Mask and protect any surface not to be cleaned.

#### Health, Safety & Environmental:

**Causes skin irritation. Causes serious eye irritation.**

Keep out of reach of children.

Wash hands thoroughly after handling.

IF ON SKIN: Wash with plenty of water/soap. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Dispose of contents/container to a licensed waste centre in accordance with local/regional/national/international regulations.



#### WARNING



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For all LTP products, remember to call our technical support

+44 (0) 1823 686213 | [www.ltp-online.co.uk](http://www.ltp-online.co.uk) | [technical@ltp-online.co.uk](mailto:technical@ltp-online.co.uk)  
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN

